OSRAM

LEDriving CANBUS CONTROL UNIT

LEDriving CANBUS CONTROL UNIT





Bypasses the vehicle's outage detection

Prevents error messages in board computers during failure detection




Removable installation by fixed clips

Faston terminals with fix wire tap connectors



3 years OSRAM guarantee, refer to www.osram.comam-guarantee for precise conditions

For more customer satisfaction



Prevents failure messages

The LEDriving CANBUS CONTROL UNIT serves as a bypass of a vehicle's lamp failure detection system when using a LED retrofit lamp. The control unit offers an easy installation and is suitable for most vehicle models with automatic lamp failure detection system. OSRAM provides a 3 year guarantee for this product.

Technical data

Product information

Application (Category and Product specific)	Accessories for LED retrofits
---	-------------------------------


General Product Information


Global order reference	LEDCCU02


Electrical Data

Power input	25 W
System wattage	21 W
Nominal wattage	21 W
Power input tolerance	±20 %

Physical Attributes & Dimensions







Diameter	16.0 mm
Product weight	23.00 g
Length	18 mm

Lifetime Data

Lifespan B3	2000 hr
Lifespan Tc	2000 hr
Guarantee	3 years

Capabilities

Technology	LED accessories 1)

 $^{^{1)}}$ Accessories for light-emitting diode application

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Date of declaration	29-10-2024	
Primary article identifier	4052899301993	
Candidate list substance 1	No declarable substances contained	
Declaration no. in SCIP database	In work	

Equipment / Accessories

- Connector clips included

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899301993	LED CANBUS CONTROL UNIT CCU02	Folding carton box 2	95 mm x 30 mm x 135 mm	0.39 dm ³	75.00 g
4052899302006	LED CANBUS CONTROL UNIT CCU02	Shipping carton box 20	198 mm x 160 mm x 146 mm	4.63 dm ³	853.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File



User instruction
LEDriving CANBUS CONTROL UNIT

Safety advice

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.













OSRAM